



# KTM TWINS

## 2008 - 2009 KTM 690 - ALL MODELS

Parts & Accessories for All KTM Twins and 690s

Thank you for purchasing the new KTM Twins Performance Aluminum Fuel Filler Neck and Cap. This product has been designed to help eliminate dirt and other foreign debris from entering your fuel tank during fueling. This product also eliminates using the ignition key to remove the fuel tank cap, speeding up re-fueling during racing applications. To reduce installation time, please review these instructions BEFORE beginning the installation process.



1. Start by removing the seat and factory fuel cap. The factory vent hose can and should be re-used with this product if you are running emissions equipment. This hose should be routed to vent to the ground in the event of a tip over. If you have purchase a cap vent, this hose will not be used.



2. Insert a clean rag or paper towel into the fuel opening BEFORE starting this next step. Failure to do so will all but assure you will drop one of these screws in the tank opening!

Remove the (3) screws holding the OEM cap base. Lift off the base and O-ring.



3. Install the new Viton O-ring as shown above, be sure to leave the rag inserted in the fuel tank opening at this time. Carefully place the filler neck into place, taking care not to loose the O-ring out of it's seating groove.



4. Install the (3) Stainless M5 x 12 Countersunk machine screws at this time. Snug all screws before tightening to assure proper O-ring seating. These screws are threaded into PLASTIC! **DO NOT OVER TIGHTEN!**



5. Remove the rag at this time. Verify there is nothing left in the opening.



6. Install the fuel cap at this time, utilizing either the factory vent hose or the purchased Cap Vent. Some re-routing of the vent hose may be necessary at this time.



7. Re-install your seat. You're Done!

